

FLAT TAPPET MENU

#66900-16

- The Crower standard .842" diameter lifter
- 97 grams, 55-59 RC hardness
- Standard pushrod seat height
- Pushrod seat height: 1.570"



#66900X980-16

- The Crower standard .842" diameter lifter
- 97 grams, 55-59 RC hardness
- Coolface Option** for reduced cam/lifter wear
- Standard pushrod seat height
- Pushrod seat height: 1.570"



#66973X980SP-16

- Crower's **premium billet lifter** (.842" dia)
- Super polished lifter face, **mirror-like finish**
- Coolface** features a .016" OD hole in lifter face
- Super **lightweight design** (71g), 64-65 RC
- Pushrod seat height: 1.570"



#66974X980SP-16

- .874" dia. Crower billet lifter, **not a casting**
- Super polish lifter face for **extreme lubricity**
- Coolface Option** and Super Hard (**64-65 RC**) face
- The **best lifter on the market**, lightweight (81g) design
- Pushrod seat height: 1.640"



#66915-16

- The Crower standard .874" diameter lifter
- 110 grams, 55-59 RC hardness
- Standard pushrod seat height
- Pushrod seat height: 1.640"



#66915X980-16

- The Crower standard .874" diameter lifter
- 110 grams, 55-59 RC hardness
- Coolface Option** for reduced cam/lifter wear
- Standard pushrod seat height
- Pushrod seat height: 1.640"



#66945X980-16

- .903" diameter
- 115 grams, 55-59 RC hardness
- Coolface Option** for reduced cam/lifter wear
- Standard Pushrod seat height
- Pushrod seat height: 1.485"



#66970X980SP-16

- .903" dia. w/ HIPPOs
- Super polished lifter face, **mirror-like finish**
- Coolface option and super hard (64-65 RC) face
- Can be used w/Sm. block Chevy, Chrysler, and AMC
- The **best lifter on the market**, lightweight (81g) design
- Pushrod seat height: 1.640"



CROWER

every part for power

